# **AES-220C**

### AUTO DEALER SOFT TOUCH CAR WASH



- Compact
- Efficient
- Powder-Coated Frame
- Designed specifically for auto dealers

AUTEC is proud to introduce our all new powder coated AES-220, the 220C. Designed for the price conscious operator, it delivers a quality wash at a lower price point. If you're interested in enhancing customer satisfaction **SPECIFICATIONS** at your dealership, the AES-220C is the system for you.

Model **AES-220C** 

**ELECTRICITY** 208/230V 40/50 AMP **3PH, 4 WIRE** 10 HP

AIR PRESSURE 100 PSI

AIR SUPPLY 5 CFM

RECOMMENDED **BAY SIZE** 34' LENGTH 16' WIDTH

> Maximum **CAR SIZE** 110" WIDTH **84" HEIGHT**

Unprecedented wash quality; profitable, trouble-free operation; and longterm efficiency and durability are attributes of **all** AUTEC systems. We ensure these high performance levels by utilizing carefully monitored production controls and by the use of superior quality components: Polyflex is standard for thorough cleaning; simple, yet durable, hydraulic operation for the most gentle vehicle surface massage; reliable, self-diagnostic, softwaredriven controls; sturdy construction with optimum structural integrity, and dependable, wet-environment operation.



2500 West Front Street • Statesville NC 28677 • 704-871-9141 • fax 704-871-9101 www.autec-carwash.com • info@autec-carwash.com

## We Make More Than Car Washes...We Make Success Stories

Features:	Benefits:
Water-based Hydraulic Operation	Specially designed water-based hydraulic fluid makes the machine environmentally friendly in all circumstances.
All Welded Frame	Welded, not bolted, for superior structural integrity, ensuring enhanced machine longevity & performance.
Dual Arm Support	Keeps arm rotation true and consistent on all four arms.
Hydraulic Operation	Variable speed hydraulic drive for smooth operation provides control of the torque and speed of each arm for effective cleaning without damage.
Direct Drive	No chains, gear boxes or belts to require maintenance.
Polyflex and Friction	Double front and rear side arms, plus our dual cloth mitter ensures that every area of a vehicle's surface is gently massaged clean with the use of polyflex (standard) or soft cloth (optional) strips lubricated with just the right volume of soap and water. Years of research and testing have determined the best sizes, lengths, cuts, cores and hardware to ensure unprecedented cleaning performance.
Split Hub Design	The lower section is wide to contour to the curved vehicle undersides. The top is slim to accommodate the tops of vans and trucks with large mirrors. We call this our "mirror-saving" hub design – ensuring safe, thorough cleaning.
Overhead Mitter	The double action, overhead mitter effectively cleans all flat surfaces without the dangers and damages once associated with top brushes.
Mitter Retract	Accommodates full or partial retract option for vehicle safety during entry and exit. (Optional)
Self-Diagnostic Computer	Self-diagnostic software monitors car wash functions.
On-Board Drive- through Rinse Arch	The On-Board Drive-through Rinse Arch allows for faster, more economical installation. *Off-Board chemical standard. *On-Board soap optional.
Hydraulic Tank Heater	Keeps hydraulic oil warm to ensure consistently smooth equipment start up.
Rear Jog Standard (Front Jog Available)	Alternately jogs out each arm to allow the opposite arm to clean across the center line of the vehicle to eliminate "skunk stripes" and help the brushes to hit those hard to reach places on the front and rear of the vehicle.

AES-220C

Can control free standing HPPS pumping stations to blast rockerpanels during drive-in.

\* NOTE: ATWC option not available on this machine.

## www.autec-carwash.com 1-800-438-3028