ATF-1 AUTEC TOUCH FREE

C-Store • Professional Car Wash • Quick Lube • Auto Dealer



AUTEC's Touch Free System - ATF-1 is a high pressure, touch free system built with AUTECnology from the ground up. Built with a stainless steel frame, stainless steel panel covers and heavy duty I-beam track, this fast, user-friendly car wash accommodates vehicles up to 90" tall and 120" wide. With programmable drive wheel speed and water based hydraulic operation, AUTEC's ATF-1 runs smooth as silk. Electric eyes establish each vehicle's profile for fast, economical, pin-pointed operation – Clean cars. Minimal waste.

Our nose and tail creep feature ensures that adequate time is spent on commonly "hard-to-clean" areas. Our 45 gpm pumping station feeds 48 zero degree nozzles on oscillating arms for advanced vehicle washing. Twenty zero degree oscillating nozzles, in the gantry, blasts wheels and rocker panels. ATF-1 includes additional chemical feed for wheels. Includes scenic graphics header panel and startup marketing support materials.

The ATF-1 comes ready for profitable add-on options like Triple Foam, Bug Buster, and Undercarriage Wash among others.



2500 West Front Street • Statesville NC 28677 • 704-871-9141 • fax 704-871-9101 www.autec-carwash.com • email - info@autec-carwash.com



MODEL ATF-1

ELECTRICITY 208/230V 3PH, 4 WIRE

CONSULT FACTORY
FOR AMPS
REQUIRED AFTER
OPTIONS ARE
SELECTED.

HIGH PRESSURE PUMPING STATION

CHEMICAL PUMP
WATER HEATER

WATER SUPPLY
45 GPM

AIR SUPPLY
5 CFM

RECOMMENDED
BAY SIZE
32' LENGTH
16' WIDTH



Rocker Panel Blaster cleans wheels and rocker panels.



Rocker Panel Blaster includes nose and tail creep feature ensures that adequate time is spent on commonly "hard-to-clean" areas



Optional Triple Foam. Colorful, fragrant, exceptional cleaning performance.



Accommodates Duallies & HumVees

Features Benefits

High Pressure 25 horsepower high pressure pumping station pumps up to 45 gpm utilizing a space-saving, belt driven design. Consult factory for power requirements based on options selected.

48 Spray Nozzles 48 oscillating, zero degree nozzles deliver up to 45 gpm. Twenty-four nozzles spray on the forward pass and 24 on the reverse.

20 Spray Nozzles In gantry to blast wheels and rocker panels.

Chemical Presoak Heated & specially formulated chemical presoak.

Chemical Presoak Heater Heats a blend of water and presoak chemical for optimum cleaning.

Water-based Hydraulics Specially designed water-based hydraulic fluid makes the machine environmentally friendly in all circumstances.

Stainless Steel Absolutely the most durable construction for dependable, long-term

operation in harsh car wash environments.

All Welded Frame Welded for superior structural integrity, ensuring enhanced

machine longevity & performance.

Hydraulic Operation Variable speed hydraulic drive for smooth operation.

Direct Drive No chains or belts to require maintenance.

Self-Diagnostic Computer Self-diagnostic software monitors car wash functions.

On-board Rinse Allows most effective and efficient rinse.

Light Package Wired for interior and exterior instructional light package.

Hydraulic Tank Heater Keeps hydraulic oil warm to ensure consistently smooth equipment

start up.

- Reliable Durable Long-Term Performance Economical, Operator-Friendly Operation
 - Profitable, Express Throughput Consumer Friendly Use Dynamic Visual Appeal
 - Strong Customer Attraction & Conservation •
- Exceptional Wash Quality with State-of-the Art Chemical and High Pressure Water Delivery
 - Environment Friendly Financing & Leasing Available •